

SMD

XF+ 1.8

Option ID 276 · XF+ · 1.88 mm pitch



REAR / SIDE PICTURES:



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

OPTICAL & PERFORMANCE

LED technology	SMD
Pixel pitch	1.875 mm
LED package	1515
Brightness	1000 nit
Refresh rate	3840 Hz
Max frame rate	60 Hz
Colour processing	26 bit
Scan direction	horizontal
Viewing angle H / V	140° / 120°

MECHANICAL

Cabinet (W x H x D)	600 x 337.5 x 58 mm
Module (W x H)	300 x 168.75 mm
Cabinet resolution	320 x 180 px
Cabinet area	0.2025 m²
Cabinet weight	7.2 kg
Cabinet material	Die-Cast
Power max / typ.	500 / 250 W/m²
Heat dissipation	1,706 BTU/h/m²
IP rating	IP30
Condition	indoor
Receiving cards / cabinet	1
Receiving card	RC G36Xi

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	-10°C~+60°C
Storage temperature	-10°C~+40°C
Working humidity	10~85%RH
AC input	100V~240V, 50~60 Hz
Typical lifetime	100000 h
Certifications	Pantone Pantone Skintone DICOM
LED configuration	Common Anode
Bond wire	Copper