


IMD

XR+ 1.9 FC

Option ID 402 · XR · 1.95 mm pitch



XR+ 500 X 500 MM CABINET: MODULE, DIE-CAST FRAME AND SIDE PROFILE

OPTICAL & PERFORMANCE

LED technology	IMD
Pixel pitch	1.95 mm
LED package	4in1
Brightness	2000 nit
Refresh rate	15360 Hz
Max frame rate	240 Hz
Colour processing	26 bit
Scan direction	horizontal
Viewing angle H / V	160° / 160°

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	-20...+60 °C
Storage temperature	20°C~+40°C
Working humidity	10~90%RH
AC input	100V~240V, 50~60 Hz
Typical lifetime	100000 h
Certifications	DICOM
LED configuration	Common Cathode
Bond wire	Alloy

MECHANICAL

Cabinet (W x H x D)	500 x 500 x 80 mm
Module (W x H)	250 x 250 mm
Cabinet resolution	256 x 256 px
Cabinet area	0.25 m²
Cabinet weight	12 kg
Cabinet material	Die-Cast
Power max / typ.	480 / 140 W/m²
Heat dissipation	1,638 BTU/h/m²
IP rating	IP45
Condition	indoor
Receiving cards / cabinet	1
Receiving card	RC G36Xi