

IMD

XF+ 0.9 FC MIP coated

Option ID 407 · XF+ · 0.94 mm pitch



REAR / SIDE PICTURES:



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

OPTICAL & PERFORMANCE

LED technology	IMD
Pixel pitch	0.9375 mm
LED package	Flipchip 4in1
Brightness	1200 nit
Refresh rate	7680 Hz
Max frame rate	120 Hz
Colour processing	26 bit
Scan direction	horizontal
Viewing angle H / V	170° / 150°

MECHANICAL

Cabinet (W x H x D)	600 x 337.5 x 58 mm
Module (W x H)	300 x 168.75 mm
Cabinet resolution	640 x 360 px
Cabinet area	0.2025 m²
Cabinet weight	7.2 kg
Cabinet material	Die-Cast
Power max / typ.	260 / 130 W/m²
Heat dissipation	887 BTU/h/m²
IP rating	IP30
Condition	indoor
Receiving cards / cabinet	2
Receiving card	RC G36Xi

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	-10°C~+60°C
Storage temperature	-10°C~+40°C
Working humidity	10~85%RH
AC input	100V~240V, 50~60 Hz
Typical lifetime	100000 h
Certifications	Pantone Pantone Skintone DICOM
LED configuration	Common Cathode
Bond wire	Wireless